PRODUCT DATA SHEET

Q8 Auto 15 K

Automatic transmission fluid

Description

Q8 Auto 15 K is an excellent automatic transmission fluid that can also be used for hydraulic systems. The lubricant has a high viscosity index and optimum fluidity at low temperature, ensuring high performance and driving comfort in different conditions. It is recommended for trucks, passenger cars, buses, off-highway, construction and military equipment.

Applications

Q8 Auto 15 K meets the requirements for automatic transmissions in GM, Ford, Allison. The lubricant can be used in automatic transmissions of most trucks, passenger cars, buses, off-highway, construction and military equipment. The lubricant is also suitable as power steering fluid and hydraulic fluid.

Benefits

- *Outstanding protection against rust and corrosion.*
- *Outstanding protection against wear and extends component life.*

Specifications, recommendations and approvals

Allison	C-4	**GM**	Dexron III H

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.8583
Kinematic Viscosity, 40 °C	D 445	mm^2/s	34.52
Kinematic Viscosity, 100 °C	D 445	mm^2/s	7.31
Brookfield Viscosity, -40 °C	D 2983	Pa.s	14.000
Flash Point, COC	D 92	°C	210
Pour Point	D 97	°C	-51

The figures above are not a specification. They are typical figures obtained within production tolerances.