

Q8 Formula Prestige V 5W-30

Ultra High Performance Low SAPS, ACEA C3 2021, API SP and VW 504.00/507.00 Baumuster 2020 engine oil.

Description

Q8 Formula Prestige V 5W-30 is a Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 5 & 6 engines. This product passed the latest VW 504.00/507.00 Baumuster 2020, MB 229.52 and BMW Longlife-04 (B48) tests. The product furthermore offers protection against Low Speed Pre-Ignition (LSPI)

Applications

Q8 Formula Prestige V 5W-30 is a Synthetic Engine Oil for Euro 5 & 6 engines for VW, Mercedes, Porsche and BMW and all cars requiring an ACEA C3 2021, API SN, SN Plus, SP and cars using Gasoline or Diesel Particulate Filter (GPF or DPf)

Benefits

- LSPI (Low Speed Pre Ignition) compatible formulation for turbocharged gasoline engines
- Superior protection for exhaust catalyst and diesel particulate filter.
- Exceptional engine protection caused by stable viscosity during total service of the oil.
- Exceptional fuel economy improvement up to 2% or more.

Specifications, recommendations and approvals

ACEA	C3	Renault	RN 0700
ACEA	Recommended for ACEA C2	Renault	RN 0710
API	SP	Stellantis	FPW 9.55535/03
BMW	Longlife-04 (B48)	VAG	VW 501.01
BMW	Longlife-19 FE	VAG	VW 502.00
Chrysler	MS-11106	VAG	VW 503.00
GM	Dexos2	VAG	VW 503.01
MB	229.31	VAG	VW 504.00 Baumuster 2020
MB	229.51	VAG	VW 505.00
MB	229.52	VAG	VW 505.01
Opel/Vauxhall	OV0401547-D30 *	VAG	VW 506.00
Opel/Vauxhall	OV0401547-G30 *	VAG	VW 506.01
PSA	B71 2290	VAG	VW 507.00 Baumuster 2020
Porsche	C30		

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	5W-30
Density, 15 °C	D 4052	g/ml	0,852
Density, 20 °C	D 4052	g/ml	0,849
Kinematic Viscosity, 40 °C	D 445	mm ² /s	69,1
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12,1
Viscosity Index	D 2270	-	174
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	3,7
Apparent Viscosity, -30 °C	D 5293	mPa.s	5600
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	234

The figures above are not a specification. They are typical figures obtained within production tolerances.