

Q8 Antifreeze Long Life K Premixed

High performance premixed long life antifreeze

Description

Q8 Antifreeze Long Life K Premixed is a superior fluid that protects against freezing, boiling and corrosion of the cooling system. The antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The long life of the Antifreeze Long Life Premixed is obtained by non-depleting corrosion inhibitors.

Applications

Q8 Antifreeze Long Life K Premixed is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

Specifications, recommendations and approvals

ASTM	D 3306	INNIO Jenbacher	TA 1000-0204
ASTM	D 4656	Jaguar Land Rover	
BS	6580	KSM	2142
Case New Holland	MAT 3624	Komatsu	KES 07.892
Caterpillar	A4.05.09.01	Liebherr	MD1-36-130
Cummins	IS Series u N14	MAN	324 Type SNF
DAF	74002	MB	325.3
Detroit Diesel	Series 50 & 60 engines	MTU	MTL 5048
Deutz	0199-99-1115/6	Mazda	MEZ MN 121 D
Deutz/MWM	0199-99-2091/8	Porsche	
GM		VAG	VW TL 774 D (G12)
Hyundai/Kia		Volvo	

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	1.113
Reserve alkalinity (pH 5.5)	D 1121	ml HCL 0.1N	6
pH	D 1287	-	8.4
Freezing Protection 50-50%	D 1177	°C	-37
Flash Point, COC	D 92	°C	>120
Colour	Visual	-	Orange

The figures above are not a specification. They are typical figures obtained within production tolerances.