

Q8 Auto CVT EVO

Synthetic CVT fluid

Description

Q8 Auto CVT EVO is an outstanding multi-vehicle Continuous Variable Transmission fluid for modern transmissions. This product is shear stable, offers extended drain intervals, excellent performance reserve and prevents slipping belts/clutches and breakdowns. It maintains high steel-steel friction and oil pressure, and provides a strong oil film.

Applications

Q8 Auto CVT EVO is applicable for CVT transmissions in passenger cars. It meets the JASO LVFA specification. The product is based on new technology and exceeds the requirements of all major OEMs such as Toyota, Nissan, Mitsubishi, Subaru, Suzuki, Hyundai, Honda, Daihatsu, Mini, BMW, Chrysler and GM.

Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.
- Excellent metal-metal friction and torque transfer
- Excellent oxidation and thermal stability
- Incorporates well balanced friction modifier system

Specifications, recommendations and approvals

BAIC	CVTF-EX1	Mitsubishi	Diaqueen SP-III
BMW/MINI	83 22 0 136 376	Mopar	CVT+4
BMW/MINI	83 22 0 429 154	Nissan	KTF-1
BMW/MINI	EZL 799	Nissan	N-CVT
BMW/MINI	EZL 799	Nissan	NS-1
BMW/MINI	EZL 799A	Nissan	NS-2
BMW/MINI	ZF CVT V1	Nissan	NS-2V
Chery	CVT	Nissan	NS-3
Chrysler	CVT+4	Opel/Vauxhall	7-speed CVT
Chrysler	NS-2	Opel/Vauxhall	95529854
DFSK	CVTF-EX1	PSA	Standard 9735EF
Daihatsu	Ammix CVTF DFE	Punch	CVTF-EX1
Daihatsu	Ammix CVTF DC	Renault	Matic CVT
Daihatsu	Ammix CVTF DFC	Renault	Matic CVT CK
Daihatsu	Fluid TC	Renault	Matic CVT FK
Dodge	CVTF+4	Renault	Matic CVT SK
Dodge	NS-2	Saturn	CVTF I-Green2
Fiat	Tutela Car CVT NG	Saturn	DEX-CVT
Fujijyuuko	i-CVTF FG	Shell	Green 1V
GM	1940713	Subaru	CV-30
GM	1940714	Subaru	ECVT
GM	CVTF I-Green2	Subaru	High Torque CVTF-LV
GM	DEX-CVT	Subaru	K0421Y0700
GM	HP CVT	Subaru	K0425Y0710
GM	VT 40	Subaru	K0425Y0711
Honda	CVT	Subaru	Lineartronic Chain CVT 3 Fluid
Honda	Fit	Subaru	Lineartronic High Torque (HT) CVT Fluid
Honda	HCF2	Subaru	Lineartronic chain CVT
Honda	HMMF	Subaru	Lineartronic chain CVT II Fluid
Honda	Jazz	Subaru	NS-2
Honda	Z-1 (CVT model)	Subaru	iCVT
Hyundai/Kia	CVT-1	Subaru	iCVT FG
Hyundai/Kia	SP-III (CVT model)	Suzuki	CVT Green 1

Idemitsu	CVTF-EX1	Suzuki	CVT Green 1V
JASO	M315 Type 1A	Suzuki	CVT Green 2
Jeep	CVT+4	Suzuki	CVTF 3320
Jeep	NS-2	Suzuki	CVTF 4401
Lexus	Fluid FE	Suzuki	CVTF TC
Lexus	Fluid TC	Suzuki	NS-2
MB	236.20	Toyota	CVTF FE
MG/Rover	EM-CVT	Toyota	CVTF TC
Mazda	JWS 3320	VAG	Audi Multitronic
Mitsubishi	CVTF ECO J4	VAG	VW G 052 180
Mitsubishi	CVTF-J1	VAG	VW G 052 516
Mitsubishi	CVTF-J4	VAG	VW TL 521 16
Mitsubishi	CVTF-J4+	VAG	VW TL 521 80
Mitsubishi	Diaqueen CVT Fluid J1	Volvo	CVT 4959
Mitsubishi	Diaqueen CVT Fluid J4	Zotye	CVT
Mitsubishi	Diaqueen CVT Fluid J4+		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,849
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	7.0
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	32.3
Viscosity Index	D 2270	-	185
Brookfield Viscosity, -40 °C	D 2983	Pa.s	10
Flash Point, COC	D 92	°C	190
Pour Point	D 97	°C	-45

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Auto CVT EVO is **1.52 kg CO₂eq / kg**.
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here



**we
take
care**