

## Q8 Bizet AW 320

Chain and chainsaw oil with excellent performance

#### **Description**

Q8 Bizet AW 320 is a chain and chainsaw oil with an excellent performance and a low pour point. It contains well balanced extreme pressure additives that offer a low oil consumption. Q8 Bizet AW 320 has a strong adhesive oil film that leads to a longer lifetime of the chain slides. Its components are carefully selected with no harmful or unpleasant odours.

#### **Applications**

Q8 Bizet AW 320 is used in chains and slides of chainsaws. It is also perfect for chains, slides and guides in industrial applications.

- Improves the durability of the equipment thanks to its characteristics
- · Low oil consumption which leads to a lower maintenance cost
- Excellent adhesiveness
- Outstanding anti-wear characteristics
- Excellent thermal durability
- · Outstanding friction diminution
- · Neutral in odor

#### Specifications & Approvals

ISO

6743-1 L-AC

#### **Properties**

	Method	Unit	Typical
ISO Viscosity Grade	-	-	320
Density, 15 °C	D 4052	g/ml	0,896
Colour	D 1500	-	L 2.0
Kinematic Viscosity, 40 °C	D 445	mm²/s	320
Kinematic Viscosity, 100 °C	D 445	mm²/s	24.3
Viscosity Index	D 2270	-	97
Total Acid Number	D 974	mg KOH/g	0.37
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	280
Copper Strip, 3 h, 100 °C	D 130	-	1
Texture	Visual	-	Stringy
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.4

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Q8 Bizet AW 320 should not be used for lubricating the engine of the chain saw.

# Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Bizet AW 320 is  $1.25\,\mathrm{kg}$  CO  $_2\mathrm{eq}$  / kg. Please contact Q80ils to learn more about the positive environmental impact, the handprint,

of this product. For more info check here

