

## Q8 Formula Top Up 5W-30

### Description

Ultra-High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil. This product offer protection against Low-Speed Pre-Ignition (LSPI) as well as compatibility with Gasoline Particulate Filters (GPF). It delivers superior fuel economy and engine protection for diesel and gasoline engines while being compatible with biofuels.

### Applications

Top Up for all passenger car brands.

### Specifications, recommendations and approvals

ACEA

API

Abarth

BMW

Chrysler

Fiat

Ford

GM

ILSAC

Jaguar Land Rover

MB

Opel/Vauxhall

PSA

Porsche

Renault

Toyota

VAG

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,861
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	69.6
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	12.0
Viscosity Index	D 2270	-	173
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	3.7
Apparent Viscosity, -30 °C	D 5293	mPa.s	5600
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	209

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Only for Top Up.