

Q8 Formula Ultra 0W-30

Synthetic ACEA A5/B5 2021, Volvo 95200377 passenger car engine oil

Description

Q8 Formula Ultra 0W-30 is a superior performance passenger car engine oil, specially designed to reduce fuel consumption and to deliver exceptional engine performance for Volvo passenger car gasoline and diesel 5, 6 and 8 cylinder engines. This product meets the performance specifications of ACEA A5/B5 2021 and Volvo 95200377.

Applications

Q8 Formula Ultra 0W-30 is suitable for use in 5, 6 & 8 cylinder Volvo engines which specify Volvo 95200377 as well as other vehicles which require ACEA A5/B5 2021.

Benefits

- Improved fuel economy.
- Outstanding oil film strength under all engine operating conditions.
- Outstanding engine protection after cold starting.
- Extended drain interval capability
- Excellent protection against rust and corrosion.

Specifications, recommendations and approvals

ACEA	A5/B5	API	SJ
API	CF	Volvo	VCC 95200377

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,86
Viscosity Grade	-	-	SAE 0W-30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	54.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.8
Viscosity Index	D 2270	-	167
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.9
Apparent Viscosity, -35 °C	D 5293	mPa.s	5660
Pour Point	D 97	°C	<-51
Flash Point, COC	D 92	°C	206

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Ultra 0W-30 is **1.36** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**