

# **Q8 Goya 1000**

Classic performance industrial gear oil

### **Description**

Q8 Goya 1000 is an advanced mineral oil that meets the current standards for gear lubricants and provides high industrial performance. Its oxidation and thermal stability guarantee a long service life of the lubricant. Q8 Goya 1000 provides an optimum wear and corrosion protection under all conditions and has a minimal downtime thanks to a high load carrying capacity.

## **Applications**

Q8 Goya 1000 is used in mid to high loaded industrial gearboxes, paper and steel mills, cement and mining, plastic extrusion and injection, aerators and agitators. It is also applied in non-gear applications including shaft couplings, screws and mid to high loaded plains and rolling contact bearings (slow to medium speed).

#### **Benefits**

- Minimizes downtime which leads to a higher maintenance efficiency
- Advanced anti-wear characteristics
- Advanced protection against corrosion
- · Highly resistant to oil deterioration

#### Specifications & Approvals

ANSI/AGMA	9005-F16	ISO	12925-1 CKC-CKD
DIN	51517-3 CLP		

# **Properties**

	Method	Unit	Typical
ISO Viscosity Grade	-	-	1000
Density, 15 °C	D 4052	g/ml	0,91
Kinematic Viscosity, 40 °C	D 445	mm²/s	1000
Kinematic Viscosity, 100 °C	D 445	mm²/s	51.5
Viscosity Index	D 2270	-	98
Pour Point	D 97	°C	-6
Flash Point, COC	D 92	°C	252
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	30/0/5
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1b
Four Ball Test, Weld Load	IP 239	N	4000
Four Ball Wear, 196 N, 54 °C, 1800 rpm	D 4172	mm	0.30
Timken, OK Load	D 2782	N	330
Mean Hertz Load	-	N	592
FZG Test, A/8.3/90	DIN 51354	load stage	>12

The figures above are not a specification. They are typical figures obtained within production tolerances.

#### Remarks

Miscible and compatible with mineral and PAO-based gear oils.

# Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Goya 1000 is **1.49** kg CO<sub>2</sub>eq / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint,

of this product. For more info check here

