

Q8 Porta 4PS

Process oil with optimum performance

Description

Q8 Porta 4PS is an advanced process oil with optimum performance and a high oxidation and thermal stability. This light coloured oil has a low aromatic and nitrogen content and minimum evaporation losses when heated. Q8 Porta 4PS improves the elasticity of the rubber components.

Applications

Q8 Porta 4PS is used in rubber and ink industry. It is applied in softeners and extenders (rubber industry). Q8 Porta 4PS is also recommended as anti-dust oil in the agriculture industry and carrier oil in the lubricants industry.

Benefits

- Reduction of product portfolio through extended lubricant applications
- Highly resistant to ageing
- Optimum thermal stability
- Low evaporation

Properties

	Method	Unit	Typical
Viscosity Grade	-	-	4PS
Density, 15 °C	D 4052	g/ml	0,811
Kinematic Viscosity, 40 °C	D 445	mm ² /s	3.95
Kinematic Viscosity, 50 °C	D 445	mm ² /s	3.2
Kinematic Viscosity, 100 °C	D 445	mm ² /s	1.49
Total Acid Number	D 974	mg KOH/g	<0.03
Pour Point	D 97	°C	-15
Flash Point, COC	D 92	°C	136
Ash	D 482	% mass	<0.01
Sulfur	D 2622	% mass	<1ppm
Carbon Residue	D 524	% mass	0.08
DMSO extract	IP 346	%	<1
Refractive Index n ₂₀ /D	D 1218	-	1.449
Aniline Point	D 611	°C	92

The figures above are not a specification. They are typical figures obtained within production tolerances.