

Q8 Rembrandt EP 00

Advanced lithium extreme pressure grease

Description

Q8 Rembrandt EP 00 is a multi-purpose lithium grease with extreme pressure properties that is designed for centralised lubrication systems. The grease has advanced anti-wear properties and excellent rust-protection when used in the presence of water. Q8 Rembrandt EP 00 is temperature resistant up to 110°C and has a smooth structure that leads to an optimum pumpability and roll stability.

Applications

Q8 Rembrandt EP 00 is applied in industrial and automotive applications. The grease is used for chassis lubrication with a centralised system (such as trucks and off-highway equipment). Q8 Rembrandt EP 00 is also suited as a lubricant for other industrial applications that are not able to retain gear oils due to poorly closed gear cases.

Benefits

- Lower downtime and an improved maintenance efficiency
- Advanced anti-wear characteristics
- Optimum roll stability
- Advanced flow properties of the grease

Specifications & Approvals

DIN

51502 KP00K-30

ISO

6743 L-XCCHB00

Properties

	Method	Unit	Typical
Soap type	-	-	Lithium
Colour	Visual	-	Brown
Consistency, NLGI No.	NLGI	-	NLGI 00
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	415
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	280
Dropping Point	D 566	°C	170
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Four Ball Test, Weld Load	IP 239	N	2450

The figures above are not a specification. They are typical figures obtained within production tolerances.