

## Q8 Schumann G 1000

Outstanding fully synthetic industrial PAO-based gear oil

### Description

Q8 Schumann G 1000 is an outstanding fully synthetic industrial gear oil based on the PAO-technology. This leads to increased energy savings and reduced oil consumptions. The Q8 Schumann G 1000 has an outstanding cold start ability and extended drain periods up to 4 times compared to mineral oils. This oil meets the current industry standards and manufacturer requirements for gear lubricants.

### Applications

Q8 Schumann G 1000 is used in industrial gear transmissions where ISO VG 1000 is required, like in paper mill calender rolls and textile calendaring applications.

### Benefits

- Limited oil consumption which generates a reduced maintenance cost
- Decreased downtime thanks to increased maintenance efficiency
- Excellent synthetic oil
- Outstanding oxidation stability
- Excellently suitable for applications in a broad temperature spectrum
- Excellent protection against wear

### Specifications & Approvals

<b>ANSI/AGMA</b>	9005-F16	<b>ISO</b>	12925-1 CKC-CKD
<b>DIN</b>	51517-3 CLP-HC	<b>ISO</b>	12925-1 CKE

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	1000
Density, 15 °C	D 4052	g/ml	0,855
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	1000
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	81.0
Viscosity Index	D 2270	-	160
Total Acid Number	D 974	mg KOH/g	0.72
Pour Point	D 97	°C	-27
Flash Point, COC	D 92	°C	288
Colour	D 1500	-	L 1.0
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	20/30/20
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.48
FZG Test, A/8.3/90	DIN 51354	load stage	>12

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Miscible and compatible with mineral and PAO-based gear oils

## Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Schumann G 1000 is **2.06** kg CO<sub>2</sub>eq / kg.*

*Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.*

*For more info check here*



**we  
take  
care**