

## Q8 Stravinsky POE 32

Synthetic refrigeration compressor oil

### Description

Q8 Stravinsky POE 32 is a synthetic refrigeration compressor oil developed with POE (Polyol Ester) base fluid. The product is recommended for use with HFC type refrigerant (such as R134a). The outstanding thermal and oxidative stability provide extended and problem-free service life.

### Applications

Reciprocating- and rotary refrigerator compressors Refrigerators, air conditioners, freezers and heat pumps Refrigerating systems handling HFC type refrigerant (such as R134a)

### Features

**Lower operational costs**

**Extended drain**

### Benefits

Superior quality to maximize compressor lifetime and improve system efficiency, thereby reducing operating costs

Exceptional thermal stability, providing extended oil drain periods

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.95
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	32
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	5.3
Total Acid Number	D 664	mg KOH/g	<0.05
Pour Point	D 97	°C	-30
Flash Point, COC	D 92	°C	>200
Appearance	Visual	-	ISO VG 32

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky POE, it is recommended to flush the compressor lubricant system.