

# Q8 T 35 SAE 140

API GL-4 manual transmission fluid

## Description

Q8 T 35 SAE 140 is an advanced manual transmission fluid. It is developed for synchromesh transmissions, offering optimal low temperature fluidity and protection under high pressure. It meets the requirements of the API GL-4 specification.

## Applications

Q8 T 35 SAE 140 is formulated for synchromesh transmissions. It meets the requirements of the API GL-4 specification.

## Benefits

- Outstanding protection against wear and extends component life.
- Outstanding protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.
- Stay-in grade shear stability

## Specifications, recommendations and approvals

API GL-4 MB 235.1

## Properties

|                             | Method | Unit               | Typical |
|-----------------------------|--------|--------------------|---------|
| Density, 15 °C              | D 4052 | g/ml               | 0,906   |
| Viscosity Grade             | -      | -                  | SAE 140 |
| Kinematic Viscosity, 40 °C  | D 445  | mm <sup>2</sup> /s | 347     |
| Kinematic Viscosity, 100 °C | D 445  | mm <sup>2</sup> /s | 25.4    |
| Viscosity Index             | D 2270 | -                  | 96      |
| Pour Point                  | D 97   | °C                 | -15     |
| Flash Point, P-M            | D 93   | °C                 | >200    |

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 35 SAE 140 is **1.25** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we  
take  
care**