

# Q8 Verdi 150

Multi-purpose circulating oil

# **Description**

Q8 Verdi 150 is an advanced multi-purpose circulating oil with a long service life. It has a high chemical and thermal stability and protects against rust and corrosion. Q8 Verdi 150 has optimum lubricating characteristics and water resistant properties.

## **Applications**

Q8 Verdi 150 is used in hydro turbines, pumps, valves and other applications that require a long service life. It is applied in a variety of industrial systems that don't need anti-wear performance. Q8 Verdi 150 is highly recommended for plain and rolling bearings, vacuum pumps, hydraulic pumps and air compressor applications.

#### **Benefits**

- Extensive lubricant applications so limited products needed
- Extends service life time thus minimal costs and maximal efficiency
- · Highly suitable for a wide range of application
- Outstanding oxidation stability
- Optimum anti-corrosion characteristics
- Optimum separation of water

# Specifications & Approvals

DIN	51506 VBL	DIN	51524-1 HL
DIN	51517-2 CL	ISO	6743-2 F

### **Properties**

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
ISO Viscosity Grade		-	150
Density, 15 °C	D 4052	g/ml	0,887
Kinematic Viscosity, 40 °C	D 445	mm²/s	150
Kinematic Viscosity, 100 °C	D 445	mm²/s	14.7
Viscosity Index	D 2270	-	97
Total Acid Number	D 974	mg KOH/g	0.12
Pour Point	D 97	°C	-24
Flash Point, COC	D 92	°C	262
Colour	D 1500	-	L 2.0
Emulsion, Distilled Water, 82.2 °C	D 1401	-	40-40-0(10)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/20/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1
Oxidation Characteristics (TOST)	D 943	hrs	> 1.500
Q panel rust preventive test, 24 hr @ 27 °C	KPI 31	Rating	
Solid Foreign Particles	Millipore, 0.45 μm	-	absent
Oxide Ash	D 482	% mass	<0.01

The figures above are not a specification. They are typical figures obtained within production tolerances.

# Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Verdi 150 is  $1.22~{\rm kg}~{\rm CO}_2{\rm eq}$  / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

