

Q8 da Vinci AM 4

Very light demoulding oil with exceptional anti-mist properties

Description

Q8 da Vinci AM 4 is a superior solvent free demoulding oil with anti-rust inhibitors and anti-mist additives to prevent inhalation of vapours. The reactive layer in this easily applicable oil creates a layer between concrete and mould and contains additives for a clean demoulding. Q8Oils claims that Q8 da Vinci provides an exceptional smooth concrete surface finish and a clean mould.

Applications

Q8 da Vinci AM 4 is used for demoulding of prefab concrete foundation piles and on-site elements such as floors, stairs and balconies. It is applied in steel and plywood moulds. Q8 da Vinci AM 4 is also used as an anti-sticking oil for asphalt plants, asphalt trucks and for cleaning tools at the work site.

Benefits

- Extremely effective demoulding operation
- Durable & reliable end product quality
- Outstanding smooth surface
- Enriched with special additives
- Light colour
- Outstanding anti-rust properties
- Easy to use
- Prevents sticking

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0,813
Kinematic Viscosity, 40 °C	D 445	mm ² /s	4.0
Pour Point	D 97	°C	-24
Flash Point, COC	D 92	°C	128
Rust Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 da Vinci range should be applied evenly and sparingly by low-pressure spray or brush onto a dry surface, ideally immediately after stripping. A second coat may be necessary when used on new timber or untreated wood.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 da Vinci AM 4 is **1.26** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**