SAFETY DATA SHEET

Q8 van Gogh 32



SECTION 1: Identific undertaking	ation of the substance/mixture and of the company/
1.1 Product identifier	
Product name	: Q8 van Gogh 32
Viscosity or Type	: ISO VG 32
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Material uses	: Lubricating oil for industrial systems
1.3 Details of the supplier of	the safety data sheet
Supplier	: Q8Oils Italia S.r.I. Via Volpedo 2 15050 Castellar Guidobono (AL) Tel. +39 02-90595.1, Fax +39 02-90076347 e-mail: Q8OilsItalia@Q8.it
Manufacturer / Distributor	: Q8Oils Italia S.r.I. Via Volpedo 2 15050 Castellar Guidobono (AL) Italy Italy Italy Italy
e-mail address of person responsible for this SDS	· SDSinfo@09 com communication proferably in English only
PCN Information contact	 SDSinfo@Q8.com, communication preferably in English only. PCNinfo@Q8.com, communication preferably in English only.
1.4 Emergency telephone nu	mber
Italy	• 900 600 702 (Tall free)
Europe	: +44 (0) 1235 239 670
Global (English only)	: +44 (0) 1865 407 333
National advisory body/Poi	
Italy	 CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA (ROMA) : 06 68593726 Az. Osp. Univ. Foggia (FOGGIA) : 800183459 Az. Osp. "A. Cardarelli" (NAPOLI) : 081-5453333 CAV Policlinico "Umberto I" (ROMA) : 06-49978000 CAV Policlinico "A. Gemelli" (ROMA) : 06-3054343 Az. Osp. "Careggi" U.O. Tossicologia Medica (FIRENZE) : 055-7947819 CAV Centro Nazionale di Informazione Tossicologica (PAZIA) : 0382-24444 Osp. Niguarda Ca' Granda (MILANO) : 02-66101029 Azienda Ospedaliera Papa Giovanni XXII (BERGAMO) : 800883300 Azienda Ospedaliera Integrata Verona (VERONA) : 80011858

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Q8 van Gogh 32

SECTION 2: Hazards	ir	lentification
Ingredients of unknown		None.
toxicity		
Ingredients of unknown ecotoxicity	:	None.
See Section 11 for more deta	ilec	information on health effects and symptoms.
2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response		Not applicable.
Storage		Not applicable.
Disposal		Not applicable.
Supplemental label elements		Contains N-1-naphthylaniline and (4-nonylphenoxy)acetic acid. May produce an allergic reaction. Safety data sheet available on request.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	-	Not applicable.
Detergents - Regulation (EC) No 648/2004	:	Not applicable.
Special packaging requiren	nen	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII		In the provided a strain of the provided and the provided a pr
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Severely refined mineral oil (C15 - C50) - Not classified.	CAS: *	≥90	Not classified.	-	[2]
N-1-naphthylaniline	REACH #: 01-2119488704-27 EC: 201-983-0 CAS: 90-30-2	<0.25	Acute Tox. 4, H302 Skin Sens. 1B, H317 STOT RE 2, H373 (blood system) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1625 mg/kg M [Acute] = 1 M [Chronic] = 1	[1]

Q8 van Gogh 32

SECTION 3: Composition/information on ingredients					
(4-nonylphenoxy)acetic acid	1	<0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg M [Acute] = 1 M [Chronic] = 1	[1]

Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1	Descri	ption	of first	aid	measures
			••••••		

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: ₩ash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	■ No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.

Q8 van Gogh 32

Specific treatments

Skin contact	 Adverse symptoms may include the following: irritation
	dryness
	cracking
Ingestion	: No specific data.

quantities have been ingested or inhaled.

: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).	
Unsuitable extinguishing media	: Do not use water jet.	
5.2 Special hazards arising	m the substance or mixture	
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burs	t.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide	
5.3 Advice for firefighters		
Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incid	ent

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials fo	r containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Date of issue/Date of revision	: 13-02-2023 Date of previous issue : 05-08-2019 Version : 1.01 4/1

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

- : Not available.
- specific : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values		
Severely refined mineral oil (C15 - C50) - Not classified.	EU OEL (Europe). TWA: 5 mg/m³ 8 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist		
procedures atmosphere or to of the ventilation protective equip the following: E the assessment limit values and atmospheres - C of exposure to c (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness of or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as uropean Standard EN 689 (Workplace atmospheres - Guidance for of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be		

Q8 van Gogh 32

SECTION 8: Exposure controls/personal protection

required.

Product/ingredient name	Туре	Exposure	Value	Population	Effects
-1-naphthylaniline	DNEL	Long term Oral	0.008 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.008 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.015 mg/	General population	Systemic
	DNEL	Long term Dermal	0.02 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.08 mg/m ³	Workers	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	3.33 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6.67 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	33 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	44 mg/m ³	Workers	Systemic
(4-nonylphenoxy)acetic acid	DNEL	Long term Oral	0.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.25 mg/ kg bw/day	General	Systemic
	DNEL	Long term Inhalation	0.43 mg/m ³		Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.76 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	4.3 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	17.6 mg/m³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls		
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measur	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		

SECTION 8: Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	 Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 mormation on basic physic	ai and chemical properties
<u>Appearance</u>	
Physical state	: Liquid. [Oily liquid.]
Appearance	: Clear.
Color	: Yellow [Light]
Odor	: Characteristic.
Odor threshold	: Not available.
Melting point/freezing point	: Not applicable.
Pour point	: <mark>,</mark> ∕2°C (10.4°F) [ASTM D 97]
Initial boiling point and boiling range	: >300°C (>572°F)
Flammability	: Not applicable.
Lower and upper explosion limit	: Not available.
Flash point	: 🗭pen cup: 220°C (428°F) [ASTM D92.]
Auto-ignition temperature	: >300°C (>572°F)
Decomposition temperature	: >300°C
рН	∶ <mark>N</mark> ot applicable.
Viscosity	: Kinematic (40°C (104°F)): 32 mm²/s (32 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 5.5 mm²/s (5.5 cSt) [ASTM D 445]
Solubility(ies)	· :

9.1 Information on basic physical and chemical properties

Solubility(ies)

Media	Result
old water hot water	Not soluble Not soluble
Partition coefficient: n-octanol/ : water	Not applicable.
	Ø.01 kPa (<0.075006 mm Hg) Ø.87 g/cm³ [15°C (59°F)] [ASTM D 4052]

Q8 van Gogh 32

SECTION 9: Physical and chemical properties

Vapor density	: Not available.
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil	LC50 Inhalation Dusts and	Rat - Male,	5.53 mg/l	4 hours
(C15 - C50) - Not classified.	mists	Female		
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
N-1-naphthylaniline	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	1625 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) - Not classified.	N/A	N/A	N/A	N/A	5.53
N-1-naphthylaniline (4-nonylphenoxy)acetic acid	1625 500	N/A N/A	N/A N/A	N/A N/A	N/A N/A

Irritation/Corrosion

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation		
Severely refined mineral oil (C15 - C50) - Not classified.	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours		
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours		
	Skin - Edema	Rabbit	0	72 hours	7 days		
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days		
N-1-naphthylaniline	Skin - Mild irritant	Rabbit	-	4 hours 5 %	-		
	Skin - Mild irritant	Rabbit	-	1008 hours 5	-		
				% I			
	Skin - Mild irritant	Rabbit	-	50 %	-		

Conclusion/Summary : Not available.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Severely refined mineral oil (C15 - C50) - Not classified.	skin	Guinea pig	Not sensitizing

Conclusion/Summary : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Severely refined mineral oil (C15 - C50) - Not classified.	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

Conclusion/Summary

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Negative - Dermal - TC	Mouse - Female	-	78 weeks

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-

Conclusion/Summary

: Not available.

: Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
№ -1-naphthylaniline	Category 2	-	blood system

Aspiration hazard

Not available.

SECTION 11: Toxicological information

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	;	No known significant effects or critical hazards.
Symptoms related to the phys	sic	al, chemical and toxicological characteristics
Eye contact	:	No specific data.

Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>		
Potential immediate effects	: Not availabl	e.
Potential delayed effects	: Not availabl	e.
<u>Long term exposure</u>		
Potential immediate effects	: Not availabl	e.
Potential delayed effects	: Not availabl	e.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m ³	4 weeks; 5 days per week
Conclusion/Summary	: Not available.			
General	: Prolonged or repeated conta	act can defat the	e skin and lead to irri	tation, cracking and/

	or dermatitis	S.
Carcinogenicity	: No known s	significant effects or critical hazards.
Mutagenicity	: No known s	significant effects or critical hazards.
Reproductive toxicity	: 🛛 known s	significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Acute NEL >100 mg/l Fresh water	Algae	72 hours
	Acute NEL >10000 mg/l Fresh water Acute NEL ≥100 mg/l Fresh water Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia Magma Fish - Pimephales promelas Daphnia - Daphnia magna	48 hours 96 hours 21 days
Conclusion/Summary	: Not available.		

12.2 Persistence and degradability

Conclusion/Summary	: Not available.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Severely refined mineral oil (C15 - C50) - Not classified.	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
N-1-naphthylaniline	4.28	1424	high

· · · · · · · · · · · · · · · · · · ·	1	2.4	Мо	bility	in soil	
---------------------------------------	---	-----	----	--------	---------	--

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods Product	;
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalogue	(EWC)

SECTION 13: Disposal considerations

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

SE CTION 45 4:

SECTION 15: Regulato	ory information
Industrial emissions : (integrated pollution prevention and control) - Air	Not listed
Industrial emissions : (integrated pollution prevention and control) - Water	Not listed
Ozone depleting substances Not listed.	<u>(1005/2009/EU)</u>
Prior Informed Consent (PIC) Not listed.	<u>) (649/2012/EU)</u>
Persistent Organic Pollutants Not listed.	<u>S</u>
Seveso Directive This product is not controlled u National regulations	nder the Seveso Directive.
Germany	
Hazard class for water : (WGK)	1
Switzerland	Not determined. Health and Safety in the workplace. Protection against risks from chemical agents. Classification Labelling and Packaging of Dangerous Products. List of work related deseases that require notification. Exempt.
International regulations Chemical Weapon Convention Not listed.	n List Schedules I, II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on Per Not listed.	r <u>sistent Organic Pollutants</u>
Rotterdam Convention on Price Not listed.	or Informed Consent (PIC)
UNECE Aarhus Protocol on Po Not listed.	<u>OPs and Heavy Metals</u>
Inventory list	
Australia :	Not determined.
Canada :	Not determined.
China :	Not determined.
Eurasian Economic Union : Japan :	Russian Federation inventory: Not determined. Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
New Zealand :	Not determined.

Date of issue/Date of revision

SECTION 15: Regulatory information

-		
Philippines	1	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States of America	:	Not determined.
Viet Nam	1	Not determined.
15.2 Chemical Safety	:	Chemical Safety Assessments for all substances in this product are either Complete

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Indicates information	ion that has changed from previously issued version.
Indicates informations and acronyms	ion that has changed from previously issued version. ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ASTM = American Society for Testing and Materials ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DIN = German Institute for Standardization DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DNEL = Derived No Effect Level DNEL = Derived No Effect Level EC50 = Half maximal effective concentration EN = European Standard (Norm) EUH statement = CLP-specific Hazard statement GHS - Globally Harmonized System of Classification and Labeling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IC50 = Half maximal inhibitory concentration INDG = International Maritime Organization LS50 = Median lethal concentration LS50 = Median lethal dose LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978, ("Marpol" = marine pollution) N/A = Not available NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration OEL = Occupational Exposure Limit PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RECH = Regulation (EC) No. 1907/2006] RID = The Regulation sconcerning the International Carriage of Dangerous Goods by Effect Level / Concentration OEL = Occupational Exposure Limit PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration REACH = Registration, cellon Noter Adverse Effect Level / Concentration NOAEL / NOAEC = No Observed Adverse Effect Lev
	SVHC = Substances of Very High Concern

SECTION 16: Other information

UN = United Nations VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

⊮ 302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Acute 1	ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 13-02-2023
Date of issue/ Date of revision	: 13-02-2023
Date of previous issue	e : 05-08-2019
Version	: 1.01
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands
Notice to seeden	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.