

Q8 Antifreeze Premixed

Premixed ethylene glycol based engine coolant

Description

Q8 Antifreeze Premixed is an excellent ethylene glycol based engine coolant. It is free from amines, phosphates and nitrites. Q8 Antifreeze Premixed is ready to use, no water needs to be added.

Applications

Q8 Antifreeze Premixed is used in coolant systems of automotive and industrial internal combustion engines during all seasons. It is also suited for some industrial heat exchanger systems.

Benefits

- Superb corrosion protection of coolant system metal compositions and solders.
- Outstanding compatibility with car paint and finishes.
- Outstanding system metal corrosion protection.
- Outstanding compatibility with system rubber seals
- All seasons type engine coolant.

Specifications, recommendations and approvals

AFNOR	NF R 15-601	FVV Heft	R 443
ASTM	D 3306	JIS	K 2234
ASTM	D 4656	SAE	J 1034
CUNA	NC 956-16	UNE	26-361-88/1

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	1,075
Colour	Visual	-	Green-blue
Freezing Protection 50-50%	D 1177	°C	-36

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Antifreeze Premixed should not be diluted with water, the product is ready for use in the engine cooling system. Replacement is recommended after 1 year with this type of engine coolant.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Antifreeze Premixed is **1.20 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

