

## Q8 Auto MV

Synthetic automatic transmission fluid

### Description

Q8 Auto MV is a superior multi-vehicle, synthetic automatic transmission fluid. Due to its fuel saving and multi-operational properties, it minimizes inventory costs. This exceptional product is compatible with vehicles that require low viscosity oil and is suitable for a wide range of European, Japanese and Korean passenger cars.

### Applications

Q8 Auto MV can be used in a wide range of European, Japanese and Korean passenger cars with automatic transmissions. The lubricant is specifically designed for ZF 6HP/8HP/9HP, MB, Aisin Warner, GM and Ford using a low viscosity automatic transmission fluid.

### Benefits

- Superior protection against wear and extends component life.
- Optimal friction characteristics even at low temperatures
- Outstanding elastomer compatibility

### Specifications, recommendations and approvals

<b>Aisin Warner</b>	JWS AW-1	<b>MB</b>	236.15
<b>BMW/MINI</b>	83 22 0 142 516	<b>MB</b>	236.17
<b>BMW/MINI</b>	83 22 0 163 514	<b>MB</b>	236.41
<b>BMW/MINI</b>	83 22 0 397 114	<b>Mazda</b>	ATF FZ
<b>Ford</b>	Mercon LV	<b>Mitsubishi</b>	ATF-J3
<b>GM</b>	Dexron VI	<b>Nissan</b>	Matic S
<b>GM</b>	GMN10060	<b>Toyota</b>	ATF WS including Toyota hybrid system
<b>Honda</b>	DW-1	<b>VAG</b>	VW G 052 533
<b>Hyundai/Kia</b>	SP-IV	<b>VAG</b>	VW G 055 005 (ZF LifeguardFluid 6)
<b>Hyundai/Kia</b>	SPH-IV	<b>VAG</b>	VW G 055 162 (ZF LifeguardFluid 6 Plus)
<b>JASO</b>	M315 Type 1A	<b>VAG</b>	VW G 055 540
<b>Jaguar Land Rover</b>	Fluid 8432	<b>VAG</b>	VW G 060 162 (ZF LifeguardFluid 8)
<b>MB</b>	236.12	<b>ZF</b>	TE-ML 09
<b>MB</b>	236.14		

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,846
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	28.5
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	5.8
Viscosity Index	D 2270	-	151
Brookfield Viscosity, -40 °C	D 2983	Pa.s	11
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	> 200

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

## Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Auto MV is **1.38** kg CO<sub>2</sub>eq / kg.*

*Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.  
For more info check here*



**we  
take  
care**