

Q8 Bizet AW 320

Chain and chainsaw oil with excellent performance

Description

Q8 Bizet AW 320 is a chain and chainsaw oil with an excellent performance and a low pour point. It contains well balanced extreme pressure additives that offer a low oil consumption. Q8 Bizet AW 320 has a strong adhesive oil film that leads to a longer lifetime of the chain slides. Its components are carefully selected with no harmful or unpleasant odours.

Applications

Q8 Bizet AW 320 is used in chains and slides of chainsaws. It is also perfect for chains, slides and guides in industrial applications.

Benefits

- Improves the durability of the equipment thanks to its characteristics
- Low oil consumption which leads to a lower maintenance cost
- Excellent adhesiveness
- Outstanding anti-wear characteristics
- Excellent thermal durability
- Outstanding friction diminution
- Neutral in odor

Specifications & Approvals

ISO 6743-1 L-AC

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	320
Density, 15 °C	D 4052	g/ml	0,896
Colour	D 1500	-	L 2.0
Kinematic Viscosity, 40 °C	D 445	mm ² /s	320
Kinematic Viscosity, 100 °C	D 445	mm ² /s	24.3
Viscosity Index	D 2270	-	97
Total Acid Number	D 974	mg KOH/g	0.37
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	280
Copper Strip, 3 h, 100 °C	D 130	-	1
Texture	Visual	-	Stringy
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.4

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Bizet AW 320 should not be used for lubricating the engine of the chain saw.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Bizet AW 320 is **1.25** kg CO₂eq / kg.*

*Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here*



**we
take
care**