

Q8 Mozart CL 70 SAE 50

High performance cylinder oil for two stroke crosshead engines

Description

Q8 Mozart CL is a high performance cylinder oil for two stroke crosshead engines operating at high pressure and high temperature conditions. TBN 70 is recommended for high sulphur fuels (>1% mass)

Applications

For lubricating the cylinders of all large slow-speed marine diesel engines.

Features

Enhanced technology

Benefits

Excellent quality base oils, maintaining a strong oil film under all load conditions

Excellent protection against rust and corrosion, protecting all metal surfaces even under extreme conditions

Properties

| | Method | Unit | Typical |
|-----------------------------|--------|--------------------|---------|
| Density, 15 °C | D 4052 | g/ml | 0.935 |
| Viscosity Grade | - | - | SAE 50 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 220 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 18.9 |
| Viscosity Index | D 2270 | - | 96 |
| Total Base Number | D 2896 | mg KOH/g | 71.3 |
| Pour Point | D 97 | °C | -12 |
| Flash Point, P-M | D 93 | °C | 198 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Mozart CL 70 SAE 50 is **1.41** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check [here](#)



**we
take
care**