

Q8 Racing 4T 10W-50

Superior motorcycle oil

Description

Q8 Racing 4T 10W-50 is a superior synthetic lubricant that enhances power performance of 4-stroke motorcycles. It contains a unique polymeric Viscosity Index improver and exceptional anti-wear additives that result in an extreme film strength. Q8 Racing 4T 10W-50 guarantees exceptional engine cleanliness, is mechanical and thermal stable and delivers non-stop peak performance in all conditions.

Applications

Q8 Racing 4T 10W-50 is used in on- and off-road motorcycles with dry and wet clutch. It is suitable for recreational devices such as all terrain vehicles (ATV) and quads. The oil exceeds the top international OEM requirements.

Benefits

- Excellent engine performance at extreme driving conditions.
- Excellent cleanliness and wear protection for all components.
- Excellent high temperature control.
- Excellent cylinder protection against scuffing wear.
- Excellent protection against rust and corrosion.

Specifications, recommendations and approvals

API	SN	JASO	MA2
API	SP		

Properties

	Method	Unit	Typical	
Density, 15 °C	D 4052	g/ml	0,857	
Viscosity Grade	-	-	10W-50	
Kinematic Viscosity, 40 °C	ISO 3104	mm²/s	121	
Kinematic Viscosity, 100 °C	D 445	mm²/s	18,2	
Viscosity Index	D 2270	-	172	
Flash Point, P-M	D 93	°C	220	
Pour Point	D 97	°C	-36	

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Racing 4T 10W-50 is **2.25** kg CO_2eq / kg . Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

