

Q8 T 750 15W-40

Heavy-duty engine oil, API CI-4 and ACEA E7 2022

Description

Q8 T 750 15W-40 is a super high performance heavy-duty engine oil. This product is designed to improve engine durability and to prevent deposit formation. It provides advanced protection against bore polishing and cam and cylinder wear, reduces maintenance costs, and prevents corrosion and foaming. It meets the requirements of API CI-4 ACEA E7 2022.

Applications

Q8 T 750 15W-40 is designed for normally aspirated, turbocharged or supercharged engines, with or without intercooling. It is recommended for most heavy-duty diesel engines for on- and off highway applications.

Benefits

- Premium protection against engine fouling due to combustion soot.
- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

Specifications, recommendations and approvals

ACEA	E7	Isuzu	
API	CF	Iveco	
API	CI-4	MAN	M 3275-1
API	SL	MB	228.3
Caterpillar	ECF-1a	MTU	Type 2
Caterpillar	ECF-2	Mack	EO-N
Cummins	CES 20071	Renault	RLD
Cummins	CES 20072	Renault	RLD-2
Cummins	CES 20076	SDMO - Kohler	KD engine series K135 & K175
Cummins	CES 20077	Scania	
Cummins	CES 20078	Tedom	258-3
DAF		Volvo	VDS-3
Deutz	DQC III-10	ZF	TE-ML 07C
Global	DHD-1		

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.876
Viscosity Grade	-	-	SAE 15W-40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	103.4
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.3
Viscosity Index	D 2270	-	138
Total Base Number	D 2896	mg KOH/g	10.5
Pour Point	D 97	°C	-33
Flash Point, P-M	D 93	°C	230
Sulfated Ash	D 874	% mass	1.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 750 15W-40 is **1.47** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**