

Q8 T 750 20W-50

Mineral API CI-4 and ACEA E7 2022 heavy duty engine oil

Description

Q8 T 750 20W-50 is a super high performance heavy duty engine oil. This product is designed to improve engine durability and to prevent deposit formation. It provides advanced protection against bore polishing and cam and cylinder wear, reduces maintenance costs and prevents corrosion and foaming. It meets the requirements of API CI-4 ACEA E7 2022.

Applications

Q8 T 750 20W-50 is designed for normally aspirated, turbocharged or supercharged engines, with or without intercooling. It is recommended for most heavy duty diesel engines for on- and off highway applications.

Benefits

- Superb protection against engine fouling due to combustion soot.
- Excellent protection against engine wear.
- Excellent protection against rust and corrosion.
- Excellent engine protection after cold start.
- Excellent protection against piston rings deposits.

Specifications, recommendations and approvals

ACEA	E7	Caterpillar	ECF-2
API	CI-4	Global	DHD-1
API	SL	Isuzu	
Caterpillar	ECF-1a	MAN	M 3275-1
Caterpillar	ECF-1a	MB	228.3

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,886
ISO Viscosity Grade	-	-	20W-50
Kinematic Viscosity, 40 °C	D 445	mm ² /s	175
Kinematic Viscosity, 100 °C	D 445	mm ² /s	19.0
Viscosity Index	D 2270	-	125
Total Base Number	D 2896	mg KOH/g	10.5
Pour Point	D 97	°C	-39
Flash Point, P-M	D 93	°C	210
Sulfated Ash	D 874	% mass	max 1.4

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 750 20W-50 is **1.44 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**