Demoulding oil



Q8 Dali 4

Light demoulding oil for cement products

Description

Q8 Dali 4 is a light demoulding oil for cement products. It is developed for tile manufacturing and forms a unique homogenous layer on the mould to provide a better quality of the surface. The light coloured Q8 Dali 4 makes it easy to inspect the quality of the moulds and doesn't smell. Extensive testing proves that the precise application quantities optimize costs and performance.

Applications

Q8 Dali 4 is used for tiles, white cement sheets, cement slates, fence posts and thin flat sections and other prefab elements of medium to higher quality.

Benefits

- Leads to an improved durability of the finished product quality
- Superior quality of the surface
- Neutral in odor
- Reliable and durable thanks to an effective demoulding operation
- Light colour
- Enriched with special additives
- Prevents sticking
- Extremely handy to apply

Properties

	Method	Unit	Typical
Appearance	Visual	-	bright & clear
Density, 15 °C	D 4052	g/ml	811
Kinematic Viscosity, 40 °C	D 445	mm²/s	4.0
Flash Point, COC	D 92	°C	128
Rust Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Dali 4 is **1.22** kg CO₂eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

