SAFETY DATA SHEET

Q8 Formula Arctic 5W-40



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Q8 Formula Arctic 5W-40

Viscosity or Type : SAE 5W-40

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Lubricating oil for automotive engines

1.3 Details of the supplier of the safety data sheet

Supplier : Kuwait Petroleum Companies in the Benelux

> Company Office: Desguinlei 100 - 8, 2018 Antwerp, Belgium Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium

Tel. +32 3 247 38 11, Fax +32 3 216 03 42

Manufacturer / Distributor : Kuwait Petroleum Belgium N.V./S.A.

Petroleumkaai 7

B-2020 Antwerp

Belgium

Q80ils Italia S.r.l. Via Volpedo 2

15050 Castellar Guidobono (AL)

CARECHEM24

e-mail address of person

responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only. **PCN** Information contact : PCNinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Europe : +44 (0) 1235 239 670 Global (English only) : +44 (0) 1865 407 333

National advisory body/Poison Center

: Poison Centre: +32 (0)70 245 245 **Belgium**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown

toxicity

: None.

Ingredients of unknown

: None.

ecotoxicity

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

General : P103 - Read carefully and follow all instructions.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Date of issue/Date of revision : 03-09-2024 : 18-11-2022 Version: 1.02 1/16 Date of previous issue

Q8 Formula Arctic 5W-40

SECTION 2: Hazards identification

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label

elements

: Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs.,

calcium salts. May produce an allergic reaction.

Safety data sheet available on request.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119493949-12 01-2119486452-34 EC: 500-393-3 CAS: 157707-86-3	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Severely refined mineral oil (C15 - C50) * - H304	-	≥10 - ≤25	Asp. Tox. 1, H304	-	[1] [2]
Severely refined mineral oil (C15 - C50) * - Not classified.	-	≤10	Not classified.	-	[2]
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	REACH #: 01-2119657973-23 EC: 272-238-5 CAS: 68784-31-6	<2.5	Eye Dam. 1, H318 Aquatic Chronic 2, H411	-	[1]
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	EC: 682-816-2 CAS: 722503-68-6	≤1	Skin Sens. 1B, H317	Skin Sens. 1, H317: C ≥ 2%	[1]

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 2/16

SECTION 3: Composition/information on ingredients

 o	
See Section 16 for	
the full text of the H	
statements declared	
above.	

Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25 CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29 CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48 CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser.

Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion Wash out mouth with water. Remove dentures if any. If material has been

> swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation dryness cracking

Ingestion : No specific data.

Date of issue/Date of revision : 03-09-2024 : 18-11-2022 Version : 1.02 3/16 Date of previous issue

Q8 Formula Arctic 5W-40

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: reat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 4/16

SECTION 6: Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

•

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Severely refined mineral oil (C15 - C50) * -	EU OEL (Europe)
H304	TWA 8 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist.
Severely refined mineral oil (C15 - C50) * - Not classified.	

Biological exposure indices

No exposure indices known.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 5/16

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	DNEL	Long term Oral	0.21 mg/ kg bw/day	General population	Systemic
,	DNEL	Long term Dermal	2.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.93 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	10.42 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	11.75 mg/ m³	General population	Systemic
	DNEL	Short term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	100 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	198.6 mg/ m³	General population	Systemic
	DNEL	Short term Inhalation	496.4 mg/ m³	Workers	Systemic
	DNEL	Short term Oral	29 mg/kg bw/day	General population	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 6/16

SECTION 8: Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Eased on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2. Gas and combination filter cartridges should comply with the European standard EN14387.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Oily liquid.]

Appearance : Clear
Color : Brown
Odor : Slight

Odor threshold : Not available.

Melting point/freezing point : Not applicable.

Pour point : <-55°C (<-67°F) [ASTM D 97]

Boiling point or initial boiling

point and boiling range

: >250°C (>482°F)

Flammability : Not applicable.

Lower and upper explosion : Not available.

limit

Flash point : Closed cup: >200°C (>392°F) [ASTM D 93]

Auto-ignition temperature : >250°C (>482°F)

Decomposition temperature : >250°C

pH : Not applicable.

Viscosity : Kinematic (40°C (104°F)): 78.6 mm²/s (78.6 cSt) [ASTM D 445]

Kinematic (100°C (212°F)): 13.3 mm²/s (13.3 cSt) [ASTM D 445]

Solubility :

Media	Result
cold water hot water	Not soluble Not soluble

Solubility in water : Not available.

Partition coefficient n-octanol/ : Not applicable.

water (log Pow) Vapor pressure

: <0.01 kPa (<0.075006 mm Hg)

Density : 0.84 g/cm³ [15°C (59°F)] [ASTM D 4052]

Relative vapor density : Not available.

Explosive properties : Not applicable.

Oxidizing properties : Not applicable.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 7/16

SECTION 9: Physical and chemical properties

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not applicable.

Oxidizing properties : Not applicable.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

Strong oxidizing materials

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	LC50 Inhalation Dusts and mists LD50 Dermal	Rat - Male, Female Rabbit	5.53 mg/l >5000 mg/kg	4 hours
Severely refined mineral oil (C15 - C50) * - Not classified.	LD50 Oral LC50 Inhalation Dusts and mists	Rat Rat - Male, Female	>5000 mg/kg 5.53 mg/l	4 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg	-
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	LD50 Oral	Rat	3.4 g/kg	-

Conclusion/Summary: Not available.

Acute toxicity estimates

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 8/16

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) * - H304	N/A	N/A	N/A	N/A	5.53
Severely refined mineral oil (C15 - C50) * - Not classified.	N/A	N/A	N/A	N/A	5.53
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	3400	N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Severely refined mineral oil (C15 - C50) * - H304	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
,	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
Severely refined mineral oil (C15 - C50) * - Not classified.	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days

Conclusion/Summary: Not available.

Respiratory or skin sensitization

Product/ingredient name	Route of exposure	Species	Result
Severely refined mineral oil (C15 - C50) * - H304	skin	Guinea pig	Not sensitizing
Severely refined mineral oil (C15 - C50) * - Not classified.	skin	Guinea pig	Not sensitizing

Conclusion/Summary: Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Severely refined mineral oil (C15 - C50) * - H304	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Severely refined mineral oil (C15 - C50) * - Not classified.	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

Conclusion/Summary: Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative - Dermal - TC	Mouse - Female	-	78 weeks

Conclusion/Summary: Not available.

Reproductive toxicity

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 9/16

Q8 Formula Arctic 5W-40

SECTION 11: Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Negative	Negative	Negative		Oral: 1000 mg/ kg	-
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-

Conclusion/Summary: Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result	
Dec-1-ene, trimers, hydrogenated Severely refined mineral oil (C15 - C50) * - H304	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1	

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data. **Inhalation** : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 10/16

Q8 Formula Arctic 5W-40

SECTION 11: Toxicological information

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m ³	4 weeks; 5 days per week
Severely refined mineral oil (C15 - C50) * - Not classified.	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m³	4 weeks; 5 days per week

Conclusion/Summary

: Not available.

General

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Acute NEL >100 mg/l Fresh water	Algae	72 hours
	Acute NEL >10000 mg/l Fresh water Acute NEL ≥100 mg/l Fresh water Chronic NEL 10 mg/l Fresh water	Daphnia - <i>Daphnia Magma</i> Fish - <i>Pimephales promelas</i> Daphnia - <i>Daphnia magna</i>	48 hours 96 hours 21 days
Severely refined mineral oil (C15 - C50) * - Not classified.	Acute NEL >100 mg/l Fresh water	Algae	72 hours
	Acute NEL >10000 mg/l Fresh water Acute NEL ≥100 mg/l Fresh water Chronic NEL 10 mg/l Fresh water	Daphnia - <i>Daphnia Magma</i> Fish - <i>Pimephales promelas</i> Daphnia - <i>Daphnia magna</i>	48 hours 96 hours 21 days

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 11/16

Q8 Formula Arctic 5W-40

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Severely refined mineral oil (C15 - C50) * - H304 Severely refined mineral oil (C15 - C50) * - Not classified.	-		Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dec-1-ene, trimers, hydrogenated	>6.5	-	High
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters,	4	-	High
zinc salts			

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes. European waste catalogue (EWC)

Waste code	Waste designation	
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils	

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 12/16

Q8 Formula Arctic 5W-40

SECTION 13: Disposal considerations

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO

instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable. Ozone depleting substances (1005/2009/EU)

Date of issue/Date of revision : 18-11-2022 : 03-09-2024 Date of previous issue Version : 1.02 13/16

Q8 Formula Arctic 5W-40

SECTION 15: Regulatory information

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants (1021/2019/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Germany

Hazard class for water : 1

(WGK)

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : Not determined.

Eurasian Economic Union: Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : All components are listed or exempted.

Republic of Korea : Not determined.

Taiwan: All components are listed or exempted.

Thailand : Not determined.
Turkey : Not determined.

United States of America : All components are active or exempted.

Viet Nam : Not determined.

15.2 Chemical Safety

Assessment

: Chemical Safety Assessments for all substances in this product are either Complete

or Not applicable.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 14/16

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

ASTM = American Society for Testing and Materials

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DIN = German Institute for Standardization

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EC = European Commission

EC50 = Half maximal effective concentration

EN = European Standard (Norm)

EUH statement = CLP-specific Hazard statement

GHS - Globally Harmonized System of Classification and Labeling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IC50 = Half maximal inhibitory concentration

IMDG = International Maritime Dangerous Goods

IMO = International Maritime Organisation

ISO = International Organization for Standardization

LC50 = Median lethal concentration

LD50 = Median lethal dose

LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration

NOEL / NOEC = No Observed Effect Level / Concentration

OECD = Organisation for Economic Co-operation and Development

OEL = Occupational Exposure Limit

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation [Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

SDS = Safety Data Sheet

SVHC = Substances of Very High Concern

STEL = Short Term Exposure Limit

TLV = Threshold Limit Value

TWA = Time Weighted Average

UFI = Unique Formula Identifier

UN = United Nations

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 15/16

Q8 Formula Arctic 5W-40

SECTION 16: Other information

H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aguatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2

Asp. Tox. 1 ASPIRATION HAZARD - Category 1

Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Skin Sens. 1B SKIN SENSITIZATION - Category 1B

Training advice : Ensure operatives are trained to minimise exposures.

Date of printing : 03-09-2024 Date of issue/ Date of : 03-09-2024

revision

Date of previous issue : 18-11-2022

Version : 1.02

Prepared by : Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 03-09-2024 Date of previous issue : 18-11-2022 Version : 1.02 16/16