

## Q8 Gear Oil V M 75W-80

Synthetic transmission fluid

### Description

Q8 Gear Oil V M 75W-80 is a superior synthetic transmission fluid, offering extended drain intervals and best-in-class performance in demanding conditions. This product provides easy gear shifting and exceptional protection in high temperature conditions due to constant film strength. Low viscosity characteristics optimize transmission efficiency and fuel economy.

### Applications

Q8 Gear Oil V M 75W-80 is especially designed for Volvo 97307 long drain intervals. This product meets the requirements of many commercial vehicle OEMs and/or gearbox manufacturers including MAN, ZF, DAF, IVECO, Eaton, Renault and Volvo.

### Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.
- Better efficiency whilst maintaining gear durability.

### Specifications, recommendations and approvals

API	GL-4	Volvo	97305
DAF		Volvo	97307 (400.000 km)
Eaton/Fuller	Europe Extended drain (300.000 km)	ZF	TE-ML 01L
Iveco		ZF	TE-ML 02L
MAN	341 Type Z4	ZF	TE-ML 08
Renault		ZF	TE-ML 16K

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,863
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	62
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	10.2
Viscosity Index	D 2270	-	151
Brookfield Viscosity, -40 °C	D 2983	Pa.s	11.0
Flash Point, P-M	D 93	°C	221
Pour Point	D 97	°C	-42

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Gear Oil V M 75W-80 is **1.21** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

