

Q8 Hartmann 46

Zinc-based hydraulic oil with outstanding stick-slip performance

Description

Q8 Hartmann 46 is a zinc-based oil that has been developed to achieve an outstanding stick-slip performance. The oil guarantees limited friction and a smooth hydraulic operation. Q8 Hartmann 46 oil has an excellent oxidation stability which leads to a longer service life of the lubricant. It is fit for use in severe working conditions.

Applications

Q8 Hartmann 46 is applied in industrial equipment in rough conditions where limited friction is needed such as big hydraulic cylinders or actuators.

Benefits

- Improves the durability of the equipment thanks to its characteristics
- Prevents sticking
- · Smooth operational properties
- Outstanding reduction of air entrainment
- Highly appropriate for applications under heavy conditions

Specifications & Approvals

 Bosch Rexroth
 RE 90220 notes
 ISO
 11158 HM

 DIN
 51524-2 HLP
 Swedish Standard
 SS 155434 AM

Eaton Brochure 03-401-2010

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	0,877
Colour	D 1500	-	1.0
Kinematic Viscosity, 40 °C	D 445	mm²/s	47
Kinematic Viscosity, 100 °C	D 445	mm²/s	6.94
Viscosity Index	D 2270	-	103
Total Acid Number	D 974	mg KOH/g	0.6
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	223
Air Release, 50 °C	D 3427	min	3
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0 (15min)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	0/10/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Oxidation Characteristics (TOST)	D 943	hrs	
Total Acid Number	D 664	mg KOH/g	0.2 after 1000h
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1b
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Hartmann 46 is **1.24** kg $\rm CO_2$ eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the

handprint, of this product. For more info check here

