

## Q8 Mahler C 15W-40

High performance gas engine oil

### Description

Q8 Mahler C is high performance gas engine oil for engines requiring Cummins CES 20074 specification. The product is suitable for four stroke gas engines operating under normal or heavy duty conditions.

### Applications

Four stroke gas engines operating under normal or heavy duty conditions.

#### Features

Enhanced technology

#### Benefits

Excellent low temperature and fluidity performance, providing outstanding protection at low temperatures and cold-start conditions

Extended drain

Excellent alkalinity reserve maintains engine performance and durability while extending oil drain interval

Engine performance

Outstanding resistance against pre-ignition and knocking

### Specifications & Approvals

Cummins CES 20074

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,884
Viscosity Grade	-	-	SAE 15W-40
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	106.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.1
Viscosity Index	D 2270	-	135
Total Base Number	D 2896	mg KOH/g	5
Pour Point	D 97	°C	-24
Flash Point, P-M	D 93	°C	190
Sulfated Ash	D 874	% mass	0.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

The original manufacturers recommendation should be followed

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Mahler C 15W-40 is **1.31** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

