

## Q8 Mozart CL 70 SAE 50

High performance cylinder oil for two stroke crosshead engines

### Description

Q8 Mozart CL is a high performance cylinder oil for two stroke crosshead engines operating at high pressure and high temperature conditions. TBN 70 is recommended for high sulphur fuels (>1% mass)

### Applications

For lubricating the cylinders of all large slow-speed marine diesel engines.

#### Features

Enhanced technology

#### Benefits

Excellent quality base oils, maintaining a strong oil film under all load conditions

Excellent protection against rust and corrosion, protecting all metal surfaces even under extreme conditions

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.935
Viscosity Grade	-	-	SAE 50
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	220
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	18.9
Viscosity Index	D 2270	-	96
Total Base Number	D 2896	mg KOH/g	71.3
Pour Point	D 97	°C	-12
Flash Point, P-M	D 93	°C	198

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Mozart CL 70 SAE 50 is **1.41** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check [here](#)



**we  
take  
care**