

## Q8 T 55 80W-90

API GL-5 axle fluid

### Description

Q8 T 55 80W-90 is an advanced heavy duty gear lubricant. The specifically selected base oils and additives offer optimum lubrication in extreme pressure and shock loading situations. This product is recommended for heavy duty axles requiring API GL-5 specification.

### Applications

Q8 T 55 80W-90 is recommended for heavy duty components such as rear axles, final drives or differentials, especially those with hypoid gears. It meets the API GL-5 specification and is applicable for on- and off-highway, construction, light and heavy duty trucks and commercial vehicles, operating under high speed/shock load, high speed/low torque or low speed/high torque conditions.

### Benefits

- Exceptional wear protection under heavy duty operating conditions.
- Outstanding protection against wear and extends component life.
- Superb gear protection under shock load conditions.
- Outstanding protection against rust and corrosion.
- Improved shear stability for a stable viscosity during use

### Specifications, recommendations and approvals

|                 |                  |                        |                  |
|-----------------|------------------|------------------------|------------------|
| API             | GL-5             | MIL                    | L-2105B          |
| Case            | MS 1316          | MIL                    | L-2105D          |
| Clark           | ALC-1 5M 7-80 KE | Rockwell International | O-76             |
| Clark           | MS-8 Rev. 1      | Volvo                  | 97310            |
| Clark           | TLC-25 3M 8-83   | ZF                     | TE-ML 05A        |
| Ford            | SM-2C-1011A      | ZF                     | TE-ML 07A        |
| Ford            | SQM-2C9002-AA    | ZF                     | TE-ML 12A        |
| Iveco           | 18-1805 RAM1     | ZF                     | <b>TE-ML 16B</b> |
| John Deere      | JDM J11E         | ZF                     | TE-ML 16C        |
| Komatsu Dresser | B22-0003         | ZF                     | <b>TE-ML 17B</b> |
| Komatsu Dresser | B22-0005         | ZF                     | <b>TE-ML 19B</b> |
| MAN             | 342 Type M1      | ZF                     | <b>TE-ML 21A</b> |
| MB              | 235.0            |                        |                  |

Color code blue = officially approved

### Properties

|                              | Method | Unit               | Typical    |
|------------------------------|--------|--------------------|------------|
| Density, 15 °C               | D 4052 | g/ml               | 0,902      |
| Density, 20 °C               | D 4052 | g/ml               | 0,898      |
| Viscosity Grade              | -      | -                  | SAE 80W-90 |
| Kinematic Viscosity, 40 °C   | D 445  | mm <sup>2</sup> /s | 146,3      |
| Kinematic Viscosity, 100 °C  | D 445  | mm <sup>2</sup> /s | 15,5       |
| Viscosity Index              | D 2270 | -                  | 100        |
| Brookfield Viscosity, -26 °C | D 2983 | Pa.s               | 135        |
| Pour Point                   | D 97   | °C                 | -27        |
| Flash Point, P-M             | D 93   | °C                 | 205        |
| Flash Point, COC             | D 92   | °C                 | 218        |

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 55 80W-90 is **1.28** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.  
For more info check here



**we  
take  
care**