

## Q8 Wagner NS 220

High performance slideway oil

### Description

Q8 Wagner NS 220 is an outstanding slideway oil with excellent wear protection through strong oil film. The oil has good demulsibility properties when in contact with water based cutting fluids, as shown in the SKC compatibility test. Q8 Wagner NS 220 provides control frictional properties, is compatible with water based metalworking fluids and offers outstanding corrosion protection of the tools.

### Applications

Q8 Wagner NS 220 is used in vertical slide ways of machine tools. This oil is also applicable in systems requiring CLP (industrial gear oils) or HLP (hydraulic oils) specifications.

### Benefits

- Increased equipment lifetime thus less downtime of machinery
- Limited products needed thanks to versatile applications of lubricants
- Protection against high pressure splashing of water based cutting fluids
- Superior decrease of friction
- High capability to separate entrained water from oil
- Superior anti-corrosion characteristics
- Highly fit for different operations
- Outstanding performance against wear

### Specifications & Approvals

ANSI/AGMA	9005-E02	DIN	51524-2 HLP
DIN	51502 CGLP	ISO	6743-13 GB
DIN	51517-3 CLP		

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	220
Density, 15 °C	D 4052	g/ml	0.895
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	222.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	19.1
Viscosity Index	D 2270	-	97
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	268
Colour	D 1500	-	2.0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1A

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Wagner NS 220 is **1.24 kg CO<sub>2</sub>eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we  
take  
care**