

## Q8 Formula Prestige V 5W-30

Ultra High Performance Low SAPS, ACEA C3, API SP and VW 504.00/507.00 Baumuster 2020 engine oil.

### Description

Q8 Formula Prestige V 5W-30 is a Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 5 & 6 engines. This product passed the latest VW 504.00/507.00 Baumuster 2020, MB 229.52 and BMW Longlife-04 (B48) tests. The product furthermore offers protection against Low Speed Pre-Ignition (LSPI)

### Applications

Q8 Formula Prestige V 5W-30 is a Synthetic Engine Oil for Euro 5 & 6 engines for VW, Mercedes, Porsche and BMW and all cars requiring an ACEA C3, API SN, SN Plus, SP and cars using Gasoline or Diesel Particulate Filter (GPF or DPF)

### Benefits

- LSPI (Low Speed Pre Ignition) compatible formulation for turbocharged gasoline engines
- Superior protection for exhaust catalyst and diesel particulate filter.
- Exceptional engine protection caused by stable viscosity during total service of the oil.
- Exceptional fuel economy improvement up to 2% or more.

### Specifications, recommendations and approvals

ACEA	C3	Porsche	<b>C30</b>
ACEA	Recommended for ACEA C2	Renault	RN 0700
API	SP	Renault	RN 0710
BMW	<b>Longlife-04 (B48)</b>	Stellantis	FPW 9.55535/03
BMW	Longlife-19 FE	VAG	VW 501.01
Chrysler	MS-11106	VAG	VW 502.00
Fiat	9.55535-S1	VAG	VW 503.00
GM	Dexos2	VAG	VW 503.01
MB	229.31	VAG	<b>VW 504.00 Baumuster 2020</b>
MB	<b>229.51</b>	VAG	VW 505.00
MB	<b>229.52</b>	VAG	VW 505.01
Opel/Vauxhall	OV0401547-D30 *	VAG	VW 506.00
Opel/Vauxhall	OV0401547-G30 *	VAG	VW 506.01
PSA	B71 2290	VAG	<b>VW 507.00 Baumuster 2020</b>

Color code blue = officially approved

\* Pending approval

### Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	5W-30
Density, 15 °C	D 4052	g/ml	0,852
Density, 20 °C	D 4052	g/ml	0,849
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	69,1
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	12,1
Viscosity Index	D 2270	-	174
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	3,7
Apparent Viscosity, -30 °C	D 5293	mPa.s	5600
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	234

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Prestige V 5W-30 is **1.26** kg CO<sub>2</sub>eq / kg.*

*Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.  
For more info check here*



**we  
take  
care**