

Q8 Formula Truck 9000 FE 5W-20

Synthetic diesel engine oil for commercial vehicles

Description

Q8 Formula Truck 9000 FE 5W-20 is an superior ultra high performance low viscosity heavy-duty engine oil. This oil provides enhanced durability, reducing wear and corrosion, and is formulated to deliver superior fuel economy for modern generation heavy-duty diesel vehicles. This lubricant delivers fuel economy savings specially for MAN and SCANIA

Applications

Q8 Formula Truck 9000 FE 5W-20 is suitable for use for all Euro VI vehicles fitted with latest generation after-treatment devices such DPFs and SCRs where use of MAN M3977 or SCANIA LDF-5 is requested

Benefits

- Extended drain interval capability
- Best-in-class engine cleanliness.
- · Fuel economy improving technology
- Superior engine cleanliness increasing engine durability.
- Superior Bio-diesel compatibility due to improved oxidation stability.

Specifications, recommendations and approvals

MAN M 3977 Scania LDF-5

Color code blue = officially approved

Properties

	Method	Unit	Typical
Viscosity Grade	-	-	SAE 5W-20
Density, 15 °C	D 4052	g/ml	0,856
Kinematic Viscosity, 40 °C	D 445	mm²/s	46.5
Kinematic Viscosity, 100 °C	D 445	mm²/s	8.1
Borderline Pumping Temperature	D 3829	°C	-36
Flash Point, P-M	D 93	°C	196
Pour Point	D 97	°C	-42
Total Base Number	D 2896	mg KOH/g	13
Sulfated Ash	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Formula Truck 9000 FE 5W-20 is **1.46** kg CO_2 eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

