

Q8 T 750 15W-40

Heavy-duty engine oil, API CI-4 and ACEA E7

Description

Q8 T 750 15W-40 is a super high performance heavy-duty engine oil. This product is designed to improve engine durability and to prevent deposit formation. It provides advanced protection against bore polishing and cam and cylinder wear, reduces maintenance costs, and prevents corrosion and foaming. It meets the requirements of API CI-4 ACEA E7.

Applications

Q8 T 750 15W-40 is designed for normally aspirated, turbocharged or supercharged engines, with or without intercooling. It is recommended for most heavy-duty diesel engines for on- and off highway applications.

Benefits

- Premium protection against engine fouling due to combustion soot.
- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

Specifications, recommendations and approvals

| | | | |
|-------------|------------|---------------|------------------------------|
| ACEA | E7 | Isuzu | |
| API | CF | Iveco | |
| API | CI-4 | MAN | M 3275-1 |
| API | SL | MB | 228.3 |
| Caterpillar | ECF-1a | MTU | Type 2 |
| Caterpillar | ECF-2 | Mack | EO-N |
| Cummins | CES 20071 | Renault | RLD |
| Cummins | CES 20072 | Renault | RLD-2 |
| Cummins | CES 20076 | SDMO - Kohler | KD engine series K135 & K175 |
| Cummins | CES 20077 | Scania | |
| Cummins | CES 20078 | Tedom | 258-3 |
| DAF | | Volvo | VDS-3 |
| Deutz | DQC III-10 | ZF | TE-ML 07C |
| Global | DHD-1 | | |

Color code blue = officially approved

Properties

| | Method | Unit | Typical |
|-----------------------------|--------|--------------------|------------|
| Density, 15 °C | D 4052 | g/ml | 0.876 |
| Viscosity Grade | - | - | SAE 15W-40 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 103.4 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 14.3 |
| Viscosity Index | D 2270 | - | 138 |
| Total Base Number | D 2896 | mg KOH/g | 10.5 |
| Pour Point | D 97 | °C | -33 |
| Flash Point, P-M | D 93 | °C | 230 |
| Sulfated Ash | D 874 | % mass | 1.5 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 750 15W-40 is **1.47** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**