

Q8 Trans XGN 75W-90

Full synthetic total driveline SAE J2360 transmission fluid

Description

Q8 Trans XGN 75W-90 is a supreme full synthetic transmission fluid designed for heavy duty driveline components requiring special low temperature fluidity. The product offers best-in-class protection against extreme pressure and wear due to exceptional stability in high as well as low temperatures. This results in optimized lubrication of hypoid and non-hypoid axles.

Applications

Q8 Trans XGN 75W-90 is designed for heavy duty components in mining or construction vehicles such as rear-axles, final drives and selected manual transmissions, requiring low temperature fluidity. It meets the latest requirements of all major OEMs such as SAE J 2360, Scania STO 2:0A FS, Volvo 97312 and MAN 342 type S1.

Benefits

- Exceptional low temperature fluidity and wide temperature operating range.
- Exceptional internal friction reduction.
- Superior axle wear protection.
- Exceptional wear protection under heavy duty operating conditions.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

| API | GL-4 | Scania | STO 1:1 G |
|--------|--------------|--------|-----------|
| API | GL-5 | Scania | STO 2:0 A |
| API | MT-1 | Scania | STO 2:0 G |
| Iveco | 18-1805 RAS1 | Volvo | 97312 |
| MAN | 341 Type E3 | ZF | TE-ML 02B |
| MAN | 341 Type Z2 | ZF | TE-ML 05A |
| MAN | 342 Type M3 | ZF | TE-ML 12L |
| MAN | 342 Type S1 | ZF | TE-ML 12N |
| MB | 235.8 | ZF | TE-ML 16F |
| MIL | PRF-2105E | ZF | TE-ML 17B |
| SAE | J 2360 | ZF | TE-ML 19C |
| Scania | STO 1:0 | ZF | TE-ML 21A |

Properties

| | Method | Unit | Typical | |
|------------------------------|----------|-------|------------|--|
| Density, 15 °C | D 4052 | g/ml | 0,871 | |
| Density, 20 °C | D 4052 | g/ml | 0,868 | |
| Viscosity Grade | SAE J306 | SAE | SAE 75W-90 | |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 84,9 | |
| Kinematic Viscosity, 100 °C | D 445 | mm²/s | 15,,3 | |
| Viscosity Index | D 2270 | - | 193 | |
| Brookfield Viscosity, -40 °C | D 2983 | Pa.s | 57 | |
| Pour Point | D 97 | °C | <-42 | |
| Flash Point, COC | D 92 | °C | 175 | |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Trans XGN 75W-90 is **1.27** kg CO_2 eq / kg. Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

