

## Q8 Gluck M

Advanced heat transfer oil

### Description

Q8 Gluck M is an advanced heat transfer oil with a well selected, highly refined paraffinic base oil. It is used for indirect closed heat transfer systems and has a high heat transfer performance over a wide temperature range. Q8 Gluck M has a long service life thanks to its oxidation stability and low carbon cracking. Its carbon deposition is reduced to a minimum to guarantee a cleaner system.

### Applications

Q8 Gluck M is used in closed heat transfer systems operating at oil film temperatures of max 330°C.

### Benefits

- Improves the durability of the equipment thanks to its characteristics
- Excellent heat dissipation
- Outstandingly heat-resistant
- High flash point
- Low residue forming
- Excellent thermal persistence

### Specifications & Approvals

ISO 6743-12 Q

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,868
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	20.22
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	4.00
Viscosity Index	D 2270	-	89
Pour Point	D 97	°C	-24
Flash Point, COC	D 92	°C	190

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Excellent low temperature flow properties (-24°C)