

Q8 T 50 M 80W-90

API GL-5 axle fluid

Description

Q8 T 50 M 80W-90 is a heavy duty gear lubricant. The product offer good lubrication in extreme pressure and shock loading situations. This product is recommended for heavy duty axles requiring API GL-5 specification.

Applications

Q8 T 50 M 80W-90 can be used in heavy-duty drive-line components such as rear axles, final drives or differentials, especially those having hypoid gears.

Benefits

- Advanced gear protection under shock load conditions.
- Outstanding elastomer compatibility
- High protection against rust and corrosion.
- High axle wear protection.

Specifications, recommendations and approvals

API	GL-5	Volvo	97310
MAN	342 Type M1	ZF	TE-ML 08
MIL	L-2105D		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.897
Kinematic Viscosity, 40 °C	D 445	mm ² /s	152,6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.9
Viscosity Index	D 2270	-	98
Brookfield Viscosity, -26 °C	D 2983	mPa.s	135
Flash Point, COC	D 92	°C	205
Pour Point	D 97	°C	-30

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 50 M 80W-90 is **1.27 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**