

## Q8 Terra 4000 UTTO CVT 75W-90

Exceptional synthetic Tractor Continuous Variable Transmission Fluid

### Description

Q8 Terra 4000 UTTO CVT 75W-90 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 Terra 4000 CVT 75W-90 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

### Applications

Q8 Terra 4000 UTTO CVT 75W-90 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant.

### Benefits

- Excellent viscosity retention providing smoothless CVT operation.
- Superb oxidation stability.
- Outstanding frictional properties for smooth brake operation.
- Excellent response of hydraulic components.
- Superb compatibility with conventional elastomers.

### Specifications, recommendations and approvals

|                  |               |        |                 |
|------------------|---------------|--------|-----------------|
| AGCO             | CVT ML 200    | Valtra | G2-B10 (XT-60+) |
| API              | GL-4          | ZF     | TE-ML 03E       |
| Case New Holland | MAT 3505      | ZF     | TE-ML 05F       |
| Case New Holland | MAT 3506      | ZF     | TE-ML 06B       |
| Case New Holland | MAT 3525      | ZF     | TE-ML 06B       |
| Case New Holland | MAT 3540      | ZF     | TE-ML 06D       |
| Caterpillar      | SATO          | ZF     | TE-ML 06E       |
| Claas            | CVT           | ZF     | TE-ML 06F       |
| Fendt            | FWN 81001     | ZF     | TE-ML 06K       |
| Fendt            | Vario         | ZF     | TE-ML 06L       |
| John Deere       | JDM J20C      | ZF     | TE-ML 06M       |
| Komatsu          | KES 07.866    | ZF     | TE-ML 06N       |
| Kubota           | UDT           | ZF     | TE-ML 06P       |
| Massey Ferguson  | CMS M 1145    | ZF     | TE-ML 06R       |
| New Holland      | NH 410-B      | ZF     | TE-ML 06S       |
| New Holland      | NH 410-C      | ZF     | TE-ML 06T       |
| Same Deutz Fahr  | UTTO          | ZF     | TE-ML 17E       |
| Valtra           | G2-08 (XT-60) | ZF     | TE-ML 21F       |

### Properties

|                              | Method   | Unit               | Typical |
|------------------------------|----------|--------------------|---------|
| Density, 15 °C               | D 4052   | g/ml               | 0,872   |
| Viscosity Grade              | SAE J306 | SAE                | 75W-90  |
| Viscosity Grade              | SAE J300 | SAE                | 15W-40  |
| Kinematic Viscosity, 40 °C   | D 445    | mm <sup>2</sup> /s | 97.6    |
| Kinematic Viscosity, 100 °C  | D 445    | mm <sup>2</sup> /s | 14.1    |
| Viscosity Index              | D 2270   | -                  | 148     |
| Brookfield Viscosity, -26 °C | D 2983   | mPa.s              | 6000    |
| Pour Point                   | D 97     | °C                 | -33     |
| Flash Point, P-M             | D 93     | °C                 | 208     |

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 4000 UTTO CVT 75W-90 is **1.33** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we  
take  
care**