

Q8 Terra 8000 Long Drain FE 10W-30

Synthetic Ultra High Performance Diesel engine oil meeting ACEA E8 / E6 / E11 / E9 / E7 and API CK-4 / CJ-4 for off-road applications

Description

The Q8 Terra 8000 Long Drain FE 10W-30 is a superior ultra high performance low SAPS synthetic engine oil for modern agricultural machinery. This product offers exceptional protection against engine wear, specifically against cam wear, and provides fuel economy improvements up to 1% or more. The product supports extended drain intervals and is compatible with biofuels. It meets the ACEA E11, E8 and API CK-4 specifications.

Applications

Q8 Terra 8000 Long Drain FE 10W-30 can be used in most Stage III / IV / V and Tier 3 / 4 diesel engines equipped with after treatment systems and operating on low sulphur diesel fuel. It is formulated for use in heavy-duty agricultural engines, including those operating under severe conditions, both in the field and on the road. Extended drain intervals can be applied based on operating conditions. The oil is compatible with engines requiring Volvo VDS-4.5 performance standards and meets ACEA E7/E8/E11, API CK-4, as well as the most important agricultural engine oil specifications.

Benefits

- Superior protection against engine wear.
- Fuel economy improvement up to 1%.
- Superior catalytic after treatment system (SCR) protection.
- Exceptional engine protection after cold start.
- Best-in-class engine cleanliness.

Specifications, recommendations and approvals

ACEA	E11 / E 9	Komatsu	EOS10W30-LA
ACEA	E7	Komatsu	KES 07.851.2
ACEA	E8 / E6	MAN	M 3677
API	CJ-4 / SN	MAN	M 3775
API	CK-4	MB	226.9
Caterpillar	ECF-3	MB	227.61
Cummins	CES 20081 / 20086	MTU	Type 2.1
Daimler Truck AG	DTFR 15C100 (MB 228.31)	MTU	Type 3.1
Daimler Truck AG	DTFR 15C110 (MB 228.51)	Mack	EO-S 4.5
Daimler Truck AG	DTFR 15C120 (MB 228.52)	Renault	RLD-3
Detroit Diesel	DFS 93K218 / 93K222	Volvo	VDS-4
Deutz	DQC IV-18 LA	Volvo	VDS-4.5
JASO	DH-2		

Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	SAE 10W-30
Density, 15 °C	D 4052	g/ml	0,861
Kinematic Viscosity, 40 °C	D 445	mm ² /s	74.3
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12.3
Viscosity Index	D 2270	-	164
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	221
Total Base Number	D 2896	mg KOH/g	10.1
Sulfated Ash	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 8000 Long Drain FE 10W-30 is **1.40** kg CO₂eq / kg.*

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**