

Q8 Vivaldi M 680

Superior circulating oil for no-twist rod mills

Description

Q8 Vivaldi M 680 is an exceptional heavy duty circulating oil specially designed for no-twist rod mills. This superior circulating oil fully meets the requirements of Morgoil no-twist rod mills and Danielli rod mills. Q8 Vivaldi M 680 offers extreme demulsibility and is the perfect product for circulating lubrication in gears and bearings.

Applications

Q8 Vivaldi M 680 is used in no-twist rod mills, hydraulic applications that require a high viscosity oil, marine and industrial gearboxes and general equipment. It is highly recommended for plain and rolling bearings. Q8 Vivaldi M 680 is suited for valves and pumps and for moderate duty spur, bevel and helical gear units.

Benefits

- Minimizes downtime which leads to a higher maintenance efficiency
- Extensive oil drain interval for a longer lubricant lifetime
- Superior separation of water
- Excellent air release
- Extreme protection against corrosion
- · Outstanding oxidation stability
- · Low residue forming
- Outstanding foam stability

Specifications & Approvals

DIN 51517-1 C ISO 6743-0 Y

Properties

| | Method | Unit | Typical |
|------------------------------------|-----------|------------|-------------|
| ISO Viscosity Grade | - | - | 680 |
| Colour | D 1500 | - | 4,5 |
| Density, 20 °C | D 4052 | g/ml | 0,899 |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 680 |
| Kinematic Viscosity, 100 °C | D 445 | mm²/s | 40 |
| Viscosity Index | D 2270 | - | 95 |
| Pour Point | D 97 | °C | -6 |
| Flash Point, COC | D 92 | °C | 255 |
| Emulsion, Distilled Water, 82.2 °C | D 1401 | - | 40-40-0(20) |
| Foam, 5 min blowing, seq. 1-2-3 | D 892 | ml | 10/20/10 |
| Foam, 10 min settling, seq. 1-2-3 | D 892 | ml | 0/0/0 |
| Rust Test, Proc. A and B, 24 h | D 665 | - | pass |
| Copper Strip, 3 h, 100 °C | D 130 | - | 1 |
| FZG Test, A/8.3/90 | DIN 51354 | load stage | >11 |

 $The figures \ above \ are \ not \ a \ specification. \ They \ are \ typical \ figures \ obtained \ within \ production \ tolerances.$

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Vivaldi M 680 is **1.29** kg CO_2 eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the

handprint, of this product. For more info check here

