

## Q8 Auto 14

Automatic transmission fluid

### Description

Q8 Auto 14 is an advanced transmission fluid for various applications, mainly heavy duty. The product is recommended for automatic transmissions meeting Dexron IID performance and the related power steering systems.

### Applications

Q8 Auto 14 is recommended for automatic transmissions meeting Dexron IID performance and the related power steering systems. It is suitable for automatic transmissions in most passenger cars, buses, construction and military equipment and in selected manual transmissions, but also as power steering and hydraulic fluid. It meets ZF, Voith, Allison, Volvo, Ford, MAN and MB specifications.

### Benefits

- Advanced protection against wear and extends component life.
- High protection against rust and corrosion.
- Cold starting improvement.

### Specifications, recommendations and approvals

Allison	C-4	MB	236.5
Ford	M2C138-CJ	MB	236.7 (DTFR 13C140)
Ford	M2C166-H	Voith	<b>H55.6335.xx</b>
Ford	M2C185-A	Voith	<b>US SB 013/118</b>
Ford	M2C186-A	Volvo	97325
GM	6137M	Volvo	97335
GM	Dexron II D	Volvo	97340
Iveco	18-1807 AG2	ZF	TE-ML 02F
Komatsu Dresser	B22-0004	ZF	TE-ML 03D
MAN	<b>339 Type L2</b>	ZF	<b>TE-ML 04D</b>
MAN	<b>339 Type V1</b>	ZF	TE-ML 09
MAN	<b>339 Type Z1</b>	ZF	<b>TE-ML 14A</b>
MB	236.1 (DTFR 13C100)	ZF	TE-ML 17C

Color code blue = officially approved

### Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0,867
Density, 15 °C	D 4052	g/ml	0,87
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	35,1
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	7,3
Viscosity Index	D 2270	-	178
Brookfield Viscosity, -40 °C	D 2983	Pa.s	32
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	214

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Auto 14 is **1.39** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.  
For more info check here



**we  
take  
care**