

Q8 Auto MV

Synthetic automatic transmission fluid

Description

Q8 Auto MV is a superior multi-vehicle, synthetic automatic transmission fluid. Due to its fuel saving and multi-operational properties, it minimizes inventory costs. This exceptional product is compatible with vehicles that require low viscosity oil and is suitable for a wide range of European, Japanese and Korean passenger cars.

Applications

Q8 Auto MV can be used in a wide range of European, Japanese and Korean passenger cars with automatic transmissions. The lubricant is specifically designed for ZF 6HP/8HP/9HP, MB, Aisin Warner, GM and Ford using a low viscosity automatic transmission fluid.

Benefits

- Superior protection against wear and extends component life.
- Optimal friction characteristics even at low temperatures
- Outstanding elastomer compatibility

Specifications, recommendations and approvals

Aisin Warner	JWS AW-1	MB	236.15
BMW/MINI	83 22 0 142 516	MB	236.17
BMW/MINI	83 22 0 163 514	MB	236.41
BMW/MINI	83 22 0 397 114	Mazda	ATF FZ
Ford	Mercon LV	Mitsubishi	ATF-J3
GM	Dexron VI	Nissan	Matic S
GM	GMN10060	Toyota	ATF WS including Toyota hybrid system
Honda	DW-1	VAG	VW G 052 533
Hyundai/Kia	SP-IV	VAG	VW G 055 005 (ZF LifeguardFluid 6)
Hyundai/Kia	SPH-IV	VAG	VW G 055 162 (ZF LifeguardFluid 6 Plus)
JASO	M315 Type 1A	VAG	VW G 055 540
Jaguar Land Rover	Fluid 8432	VAG	VW G 060 162 (ZF LifeguardFluid 8)
MB	236.12	ZF	TE-ML 09
MB	236.14		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,846
Kinematic Viscosity, 40 °C	D 445	mm ² /s	28.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	5.8
Viscosity Index	D 2270	-	151
Brookfield Viscosity, -40 °C	D 2983	Pa.s	11
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	> 200

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Auto MV is **1.38** kg CO₂eq / kg.*

*Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here*



**we
take
care**