

Q8 Bach XAF 22

High performance, neat metal cutting oil

Description

Q8 Bach XAF 22 is a cost effective chlorine free, active neat cutting oil. It has high performance additives providing high oxidation stability, long tool life, high removal performance with high surface finish of work pieces.

Applications

General machining and more severe operations of cast iron, steel and stainless steels.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from water entry, frost and direct sunlight.

There is risk of staining of copper and copper alloys. In some applications it can be used for machining aluminium and magnesium.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.87
Kinematic Viscosity, 40 °C	D 445	mm ² /s	23
Pour Point	D 97	°C	-15
Flash Point, COC	D 92	°C	210
Colour	D 1500	-	1
Copper Strip, 3 h, 100 °C	D 130	-	4
Four Ball Test, Weld Load	IP 239	kg	520

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Bach XAF 22 is **1.30** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**