

## Q8 Brahms 7001

Fluid for light duty forming and high speed punching

### Description

Very low viscosity, chlorine-free ferrous and non-ferrous forming oil with excellent evaporation properties.

### Applications

Q8 Brahms 7001 is recommended for light duty forming operations with low residue.

### User instructions

In order to preserve the integrity of this product, drums should be stored inside a building protected from frost and direct sunlight.

### Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

### Properties

	Method	Unit	Typical
Appearance	Visual	-	bright & clear
Density, 15 °C	D 4052	g/ml	0.75
Flash Point, COC	D 92	°C	75
Kinematic Viscosity, 20 °C	D 445	mm <sup>2</sup> /s	1.7

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Brahms 7001 is **1.22** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we  
take  
care**