

Q8 Chain Oil FG 220

Chain and chainsaw oil

Description

Q8 Chain Oil FG 220 is a chain and chainsaw oil that offers good wear protection through the adhesive oil film. It protects against corrosion and rust and is used in a standard range of temperatures.

Applications

Q8 Chain Oil FG 220 is used in chains and slides of chainsaws. It is perfect for chains, slideways and guides in industrial applications.

Benefits

- Effortless operation thanks to its characteristics
- Advanced adhesive properties
- High protection against wear
- Advanced protection against rust

Specifications & Approvals

ISO 6743-1 L-AC

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	220
Texture	Visual	-	Stringy
Kinematic Viscosity, 40 °C	D 445	mm ² /s	220
Flash Point, COC	D 92	°C	> 200

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Chain Oil FG 220 should not be used for lubricating the engine of the chain saw.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Chain Oil FG 220 is 1.21 kg CO₂eq / kg.
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here

