

Q8 Dynobear 32

Excellent multi-purpose circulating oil

Description

Q8 Dynobear 32 is an excellent multi-purpose circulating lubricant developed for machine tools and general equipment. It has a certain additive that reduces friction and eliminates stick-slip and judder that might occur in mechanical and hydraulic machines. Q8 Dynobear 32 has outstanding rust- and corrosion protection, excellent anti-wear characteristics and high chemical and thermal stability.

Applications

Q8 Dynobear 32 is applied in medium duty hydraulic systems. Q8 Dynobear range is highly recommended for machine tools and general equipment lubrication. It is suited for headstocks, carriage ways, cross feeds saddles and automatic pressures fed slideway lubricators.

Benefits

- Decreased downtime thanks to increased maintenance efficiency
- Limited products needed thanks to versatile applications of lubricants
- Excellent decrease of friction
- Prevents sticking
- Extremely fit for different operations

Specifications & Approvals

DIN	51517-2 CL	ISO	6743-2 F
DIN	51524-1 HL		

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0,869
Kinematic Viscosity, 40 °C	D 445	mm ² /s	32.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	5.4
Viscosity Index	D 2270	-	102
Flash Point, COC	D 92	°C	216
Colour	D 1500	-	L 0.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Dynobear 32 is 1.22 kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

