

# Q8 Formula Excel Long Life 5W-40

Synthetic ACEA A3/B4 passenger car engine oil

## Description

*Q8* Formula Excel Long Life 5W-40 is an allround high SAPS high-performance engine oil for passenger cars and light duty commercial vehicles. The lubricant guarantees advanced engine protection, and presents optimum cold weather starting properties. It is designed to counter sludge formation and meets the ACEA A3/B4 specification.

### **Applications**

*Q8* Formula Excel Long Life 5W-40 is developed for passenger cars and vans with normally aspirated or turbocharged gasoline, LPG or (direct injection) diesel engines. It is especially recommended for high performance, multi-valve engines with a catalyst. This versatile oil is an all season product that is suitable for different driving conditions. Especially recommended for Mercedes-Benz.

#### Benefits

- Outstanding oil film strength under all engine operating conditions.
- Outstanding engine protection after cold starting.
- Excellent protection against rust and corrosion.
- Outstanding friction reduction.

#### Specifications, recommendations and approvals

ACEA	A3/B4	PSA	B71 2296
API	CF	Porsche	A40
API	SN	Renault	RN 0700
BMW	Longlife-01	Renault	RN 0710
GM	LL-B-025	VAG	VW 502.00
МВ	229.3	VAG	VW 505.00
MB	229.5	Volvo	VCC 95200356

Color code blue = officially approved

### **Properties**

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,85
Viscosity Grade	-	-	SAE 5W-40
Kinematic Viscosity, 40 °C	D 445	mm²/s	81.9
Kinematic Viscosity, 100 °C	D 445	mm²/s	13.9
Viscosity Index	D 2270	-	176
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5
Pour Point	D 97	°C	-39
Flash Point, P-M	D 93	°C	221
Borderline Pumping Temperature	D 3829	°C	-35
Apparent Viscosity, -30 °C	D 5293	mPa.s	6600

The figures above are not a specification. They are typical figures obtained within production tolerances.

# Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Excel Long Life 5W-40 is **1.23** kg  $CO_2eq / kg$ . Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

