

## Q8 Formula Ultra V R 0W-20

Synthetic Volvo VCC RBS0-2AE passenger car engine oil

### Description

Q8 Formula Ultra V R 0W-20 is a superior low SAPS passenger car engine oil for Volvo Euro 6 engines. This lubricant offers 3,4% fuel saving according to the M 111 fuel economy test, extends oil drain intervals and provides ultimate protection against wear, rust and deposits. The low SAPS technology for Euro 6 exhausts provides best-in-class protection for aftertreatment system

### Applications

Q8 Formula Ultra V R 0W-20 is especially developed for Volvo Euro 6 passenger car engines requiring Volvo VCC RBS0-2AE

### Benefits

- Exceptional fuel economy improvement up to 3.4%.
- Exceptional engine protection after cold starting.
- Superior protection for SCR catalyst and diesel particulate filter.
- Extended drain interval capability
- Superior viscosity index providing strong lubricant film at all operating conditions.

### Specifications, recommendations and approvals

API SN Volvo VCC RBS0-2AE

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,845
ISO Viscosity Grade	-	-	0W-20
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	48.7
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	9.0
Viscosity Index	D 2270	-	173
Apparent Viscosity, -35 °C	D 5293	mPa.s	5700
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	204
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.6

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Ultra V R 0W-20 is **2.11 kg CO<sub>2</sub>eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we  
take  
care**