PRODUCT DATA SHEET

Q8 Garden Pro Synt 4T 5W-30

Superior garden oil

Description

Q8 Garden Pro Synt 4T 5W-30 is a superior synthetic multigrade lubricant for garden equipment. It guarantees an exceptional performance in both air and water cooled engines. Q8 Garden Pro Synt 4T 5W-30 has been enriched with unique components that improve lubricity and enhance detergency and cleanliness. The reliable garden oil offers an extreme wear protection.

Applications

Q8 Garden Pro Synt 4T 5W-30 is used in all 4-stroke gasoline engines of garden equipment such as lawn mowers, rider mowers and snow blowers. It is a reliable lubricant that covers a broad range of applications and can be used in the most severe conditions.

Specifications, recommendations and approvals

API	CF	**API**	SL

Properties

	Method	Unit	Typical
Density, 15 °C	*D 4052*	*g/ml*	*0,851*
Viscosity Grade	*-*	*-*	*5W-30*
Kinematic Viscosity, 40 °C	*ISO 3104*	*mm²/s*	*64.3*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*11.3*
Viscosity Index	*D 2270*	*-*	*169*
Apparent Viscosity, -30 °C	*D 5293*	*mPa.s*	*4300*
Flash Point, P-M	*D 93*	*°C*	*237*
Pour Point	*D 97*	*°C*	*-36*
Sulfated Ash	*D 874*	*% mass*	*1.2*

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Garden Pro Synt 4T 5W-30 is **1.34** kg CO_2eq / kg.*
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here

we take care