

Q8 Hunt 32

Sustainable hydraulic fluid

Description

Q8 Hunt 32 is a sustainable hydraulic fluid for a wide range of hydraulic applications. By using this fluid, natural resources will be saved and the carbon footprint will significantly drop compared to common hydraulic oils. Q8 Hunt 32 meets the industrial hydraulic standard DIN 51524-2 HLP thanks to its combination of purified base oils and carefully selected additives.

Applications

Q8 Hunt 32 is used in a wide range of industrial hydraulic applications. The sustainable lubricant is also applied in hydraulic systems operating in winter conditions (up to -27°C) and in mobile hydraulic systems such as cranes, excavators and other off-road equipment.

Benefits

- Lower downtime and an improved maintenance efficiency
- Includes zinc-based additives
- Optimum wear protection
- High filtration properties
- Limited impact on the environment
- Highly environmental sustainable

Specifications & Approvals

DIN 51524-2 HLP ISO 11158 HM

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0.858
Kinematic Viscosity, 40 °C	D 445	mm ² /s	31.4
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	5.6
Viscosity Index	D 2270	-	>114
Flash Point, COC	D 92	°C	230
Pour Point	D 97	°C	-27
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.